NSN 5305-01-323-3784

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-323-3784 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.425 inches **Fastener Length:** Between 2.285 inches and 2.315 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.449 inches and 0.507 inches **Grip Diameter:** Between 0.2485 inches and 0.2495 inches **Internal Drive Style:** Offset cruciform (torque set) **Thread Diameter:** 0.250 inches **Grip Length:** Between 1.865 inches and 1.885 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 180000 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Surface Finish:** 32.0 microinches threads Material: Titanium alloy uns r56400 **Material Specification:** Ams 4971 assn standard single material response **Thread Series Designator:** Unjf **Specification Data:** 80205-nas1974 professional/industrial association standard Shelf Life: N/a **Unit Of Measure:**

Demilitarization:

No

NSN 5305-01-323-3784

Close Tolerance Screw - Page 2 of 2



Fiig:

A003b0