NSN 5305-01-323-3898

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-323-3898

view Offiline at https://aerobasegroup.com/hsh/osos-01-525-5050
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 1.413 inches and 1.531 inches
Fastener Length:
Between 1.484 inches and 1.531 inches
Head Style:
Hexagon
Head Height:
Between 0.125 inches and 0.140 inches
Width Between Flats:
Between 0.367 inches and 0.376 inches
Internal Drive Style:
Cross recess type 1
Thread Diameter:
0.250 inches
Thready Qty Per Inch (tpi):
28
Min. Tensile Strength (psi):
160000 pounds per square inch
Screw Material:
Iron alloy 660
Screw Material Specification:
Ams 5731 assn standard single material response or ams 5737 assn standard single material response
Screw Surface Treatment:
Passivate
Screw Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Bearing Surface Of Head Surface Finish:
32.0 microinches
Shank Surface Finish:
32.0 microinches
Thread Surface Finish:
32.0 microinches
Thread Series Designator:
Unjf
Specification Data:
80205-nas1802 professional/industrial association standard
Shelf Life:
N/-

N/a

NSN 5305-01-323-3898

Machine Screw - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A500d0