NSN 5305-01-323-4153

Close Tolerance Screw - Page 1 of 2

AeroBase

View Online at https://aerobasegroup.com/nsn/5305-01-323-4153

| Thread Class: |
|--|
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 0.363 inches |
| Fastener Length: |
| Between 0.786 inches and 0.816 inches |
| Head Style: |
| Pan |
| Head Diameter: |
| Between 0.360 inches and 0.374 inches |
| Head Height: |
| Between 0.115 inches and 0.125 inches |
| Locking Feature: |
| Patch threads |
| Grip Diameter: |
| Between 0.1890 inches and 0.1895 inches |
| Internal Drive Style: |
| Torque-set ribbed |
| Thread Diameter: |
| 0.190 inches |
| Grip Length: |
| Between 0.428 inches and 0.448 inches |
| Thready Qty Per Inch (tpi): |
| 32 |
| Min. Tensile Strength (psi): |
| 180000 pounds per square inch |
| Surface Finish: |
| 32.0 microinches threads |
| Product Name: |
| Navy special project |
| Material: |
| Titanium alloy uns r56400 |
| Material Specification: |
| Ams 4928 assn standard single material response or ams 4967 assn standard single material response |
| Thread Series Designator: |
| Unjf |
| Specification Data: |
| 80205-nas1578 professional/industrial association standard |
| Shelf Life: |
| N/a |

NSN 5305-01-323-4153

Close Tolerance Screw - Page 2 of 2

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0

