## NSN 5305-01-323-5546

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-323-5546 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.750 inches **Fastener Length:** Between 0.970 inches and 1.000 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.218 inches and 0.226 inches **Head Height:** Between 0.134 inches and 0.138 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.138 inches Width Across Flats: Between 0.109 inches and 0.111 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 180000 pounds per square inch Hardness Rating: 38.0 rockwell c and 45.0 rockwell c Minimum Yield Strength: 155000 pounds per square inch Color: Black Material: Steel **Surface Treatment:** Oxide **Surface Treatment Specification:** Mil-c-13924, cl1 military specification single treatment response **Thread Series Designator:** Unrc **Specification Data:** 

80205-nas1352 professional/industrial association standard

Shelf Life:

N/a

## NSN 5305-01-323-5546

Socket Head Cap Screw - Page 2 of 2



	• -		
In	ıŧ	( )t	Measure:

--

Demilitarization:

No

Fiig:

A003b0

## Mil-std (military Standard):

Mil-c-13924 spec.