

View Online at <https://aerobasegroup.com/nsn/5305-01-324-8503>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 1.127 inches and 1.250 inches

**Fastener Length:**

Between 1.210 inches and 1.250 inches

**Head Style:**

Flat chamfer

**Head Diameter:**

Between 0.550 inches and 0.562 inches

**Head Height:**

Between 0.368 inches and 0.375 inches

**Width Between Flats:**

Between 0.312 inches and 0.316 inches

**Locking Feature:**

Patch or strip or pellet

**Internal Drive Style:**

Err-090

**Thread Diameter:**

0.375 inches

**Width Across Flats:**

Between 0.312 inches and 0.316 inches

**Thready Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

180000 pounds per square inch

**Hardness Rating:**

Between 39.0 rockwell c and 45.0 rockwell c

**Screw Material:**

Steel

**Locking Feature Material:**

Plastic polyamide

**Screw Surface Treatment:**

Oxide

**Screw Surface Treatment Specification:**

Mil-c-13924 cl 1 military specification single treatment response

**Color:**

Black

**Thread Series Designator:**

Unrf

**Specification Data:**

80205-nas1351 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A500d0

**Mil-std (military Standard):**

Mil-c-13924 spec.