

View Online at <https://aerobasegroup.com/nsn/5305-01-324-8503>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 1.127 inches and 1.250 inches

Fastener Length:

Between 1.210 inches and 1.250 inches

Head Style:

Flat chamfer

Head Diameter:

Between 0.550 inches and 0.562 inches

Head Height:

Between 0.368 inches and 0.375 inches

Width Between Flats:

Between 0.312 inches and 0.316 inches

Locking Feature:

Patch or strip or pellet

Internal Drive Style:

Err-090

Thread Diameter:

0.375 inches

Width Across Flats:

Between 0.312 inches and 0.316 inches

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

180000 pounds per square inch

Hardness Rating:

Between 39.0 rockwell c and 45.0 rockwell c

Screw Material:

Steel

Locking Feature Material:

Plastic polyamide

Screw Surface Treatment:

Oxide

Screw Surface Treatment Specification:

Mil-c-13924 cl 1 military specification single treatment response

Color:

Black

Thread Series Designator:

Unrf

Specification Data:

80205-nas1351 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A500d0

Mil-std (military Standard):

Mil-c-13924 spec.