

View Online at <https://aerobasegroup.com/nsn/5305-01-324-8962>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.800 inches

**Fastener Length:**

4.485 inches

**Head Style:**

Pan no. 2

**Head Diameter:**

Between 1.202 inches and 1.212 inches

**Head Height:**

0.525 inches

**Shoulder Diameter:**

0.8730 inches first shoulder and 0.8745 inches first shoulder

**Shoulder Length:**

3.435 inches first shoulder and 3.445 inches first shoulder

**Internal Drive Style:**

Square

**End Application:**

Clampup, outboard bombrack attach, cft f15 acft

**Thread Diameter:**

0.500 inches

**Width Across Flats:**

0.378 inches

**Features Provided:**

Bushing

**Thready Qty Per Inch (tpi):**

20

**Shoulder Shape:**

Round first shoulder

**Special Features:**

Bushing fits over shoulder of screw adjacent to head; bushing material is beryllium-copper alloy per federal specification qq-c-530, alloy 173, cond ht; 0.8719/0.8727 in. Inside dia, 1.202/1.212 in.O.D., 0.655/0.665 in. Lg

**Material:**

Steel comp xm-13

**Material Specification:**

Ams 5629 assn standard single material response

**Surface Treatment:**

Nickel

**Surface Treatment Specification:**

P.S.13105 class 2, cage76301 mfr ref single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0