

View Online at <https://aerobasegroup.com/nsn/5305-01-324-8962>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.800 inches

Fastener Length:

4.485 inches

Head Style:

Pan no. 2

Head Diameter:

Between 1.202 inches and 1.212 inches

Head Height:

0.525 inches

Shoulder Diameter:

0.8730 inches first shoulder and 0.8745 inches first shoulder

Shoulder Length:

3.435 inches first shoulder and 3.445 inches first shoulder

Internal Drive Style:

Square

End Application:

Clampup, outboard bombrack attach, cft f15 acft

Thread Diameter:

0.500 inches

Width Across Flats:

0.378 inches

Features Provided:

Bushing

Thready Qty Per Inch (tpi):

20

Shoulder Shape:

Round first shoulder

Special Features:

Bushing fits over shoulder of screw adjacent to head; bushing material is beryllium-copper alloy per federal specification qq-c-530, alloy 173, cond ht; 0.8719/0.8727 in. Inside dia, 1.202/1.212 in.O.D., 0.655/0.665 in. Lg

Material:

Steel comp xm-13

Material Specification:

Ams 5629 assn standard single material response

Surface Treatment:

Nickel

Surface Treatment Specification:

P.S.13105 class 2, cage76301 mfr ref single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0