NSN 5305-01-325-5992

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-325-5992 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.406 inches **Fastener Length:** Between 0.953 inches and 0.983 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.376 inches and 0.385 inches **Grip Diameter:** Between 0.1885 inches and 0.1895 inches **Internal Drive Style:** Offset cruciform (torque set) **Thread Diameter:** 0.190 inches **Grip Length:** Between 0.552 inches and 0.572 inches **Features Provided:** Cetyl alcohol lubricant Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 125000 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Special Features:** Cetyl alcohol per mil-l-87132 type 1, cl b Material: Nickel alloy 718 **Surface Treatment:** Aluminum **Surface Treatment Specification:** Mil-c-83488 type 2 cl 3 military specification single treatment response **Thread Series Designator:** Unjf Shelf Life:

N/a **Unit Of Measure:**

NSN 5305-01-325-5992

Close Tolerance Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-83488 spec.