## NSN 5305-01-325-8384

Assembled Washer Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-325-8384 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.620 inches and 0.720 inches **Fastener Length:** Between 2.250 inches and 2.280 inches **Head Style:** Flat extended washer **Head Diameter:** 0.287 inches **Head Height:** Between 0.242 inches and 0.252 inches **Extended Washer Diameter:** Between 0.418 inches and 0.438 inches **Extended Washer Thickness:** Between 0.055 inches and 0.065 inches **Spline Major Diameter:** 0.287 inches **Washer Quantity:** 1 **Internal Drive Style:** Torx **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 **Hardness Rating:** 42.0 rockwell c primary washer and 46.0 rockwell c primary washer **Primary Washer Outside Diameter:** Between 0.495 inches and 0.508 inches **Primary Washer Style:** Dome internal teeth **Primary Washer Material Thickness:** 0.039 inches Material: Steel fastener

**Material Specification:** 

Sae j429 gr8 assn standard single material response fastener

**Surface Treatment:** 

Dichromate zinc fastener

## NSN 5305-01-325-8384

Assembled Washer Screw - Page 2 of 2



G-4345m cagec 16764 mfr ref single treatment response fastener

**Thread Series Designator:** 

Unf

Shelf Life:

N/a

**Unit Of Measure:** 

\_\_

Demilitarization:

No

Fiig:

A003b0