NSN 5305-01-326-0112

Machine Screw - Page 1 of 2

Between 0.169 inches and 0.250 inches

Thread Class:

Right-hand

Thread Length:

Thread Direction:

Fastener Length:

За



View Online at https://aerobasegroup.com/nsn/5305-01-326-0112

| Between 0.219 inches and 0.250 inches |
|---|
| Head Style: |
| Pan |
| Head Diameter: |
| Between 0.178 inches and 0.183 inches |
| Head Height: |
| Between 0.059 inches and 0.069 inches |
| Locking Feature: |
| Patch or pellet or strip |
| Internal Drive Style: |
| Cross recess type 1 |
| Thread Diameter: |
| 0.112 inches |
| Thready Qty Per Inch (tpi): |
| 40 |
| Min. Tensile Strength (psi): |
| 160000 pounds per square inch |
| Screw Material: |
| Iron alloy 660 |
| Locking Feature Material: |
| Plastic polyamide |
| Screw Material Specification: |
| Ams5737 assn standard single material response |
| Screw Surface Treatment: |
| Passivate |
| Screw Surface Treatment Specification: |
| Qq-p-35 federal specification single treatment response |
| Bearing Surface Of Head Surface Finish: |
| 32.0 microinches |
| Shank Surface Finish: |
| 32.0 microinches |
| Thread Surface Finish: |
| 32.0 microinches |
| Thread Series Designator: |
| Unjc |
| |

NSN 5305-01-326-0112

Machine Screw - Page 2 of 2



| Specification D | ata: |
|-----------------|------|
|-----------------|------|

80205-nas1191 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A500d0