## NSN 5305-01-326-0115

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-326-0115 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 1.751 inches and 1.875 inches **Fastener Length:** Between 1.813 inches and 1.875 inches **Head Style:** Fillister **Head Diameter:** Between 0.221 inches and 0.226 inches **Head Height:** Between 0.074 inches and 0.086 inches **Internal Drive Style:** Torque set **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch **Hardness Rating:** Between 36.0 rockwell c and 40.0 rockwell c **Screw Material:** Iron alloy 660 **Screw Material Specification:** Ams5737 assn standard single material response **Screw Surface Treatment: Passivate Screw Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unjf **Specification Data:** 80205-nas1101 professional/industrial association standard Shelf Life: N/a **Unit Of Measure:** 

**Demilitarization:**No

## NSN 5305-01-326-0115

Machine Screw - Page 2 of 2



Fiig:

A500d0