

View Online at <https://aerobasegroup.com/nsn/5305-01-326-9637>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.648 inches and 0.750 inches

**Fastener Length:**

Between 0.719 inches and 0.750 inches

**Head Style:**

Fillister

**Head Diameter:**

Between 0.389 inches and 0.414 inches

**Head Height:**

Between 0.219 inches and 0.237 inches

**Internal Drive Style:**

Slot

**Thread Diameter:**

0.250 inches

**Thready Qty Per Inch (tpi):**

28

**Screw Material:**

Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316 or steel comp 384

**Screw Material Specification:**

Aisi assn standard all material responses

**Screw Surface Treatment:**

Passivate

**Screw Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Special Features:**

Bearing surface to shank hole center 0.670 in. And shank unthreaded hole diameter 0.062 in. Min 0.065 in. Max

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A500d0