

View Online at <https://aerobasegroup.com/nsn/5305-01-327-0362>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.340 inches

**Fastener Length:**

Between 0.858 inches and 0.906 inches

**Head Style:**

Hexagon

**Head Height:**

Between 0.105 inches and 0.120 inches

**Width Between Flats:**

Between 0.305 inches and 0.314 inches

**Hole Diameter:**

Between 0.046 inches and 0.056 inches

**First Diameter From Head:**

0.130 inches

**Distance From Largest Bearing Surface Of Head To End Of First Diameter:**

Between 0.728 inches and 0.776 inches

**Internal Drive Style:**

Cross recess type 1

**Thread Diameter:**

0.190 inches

**Hole Quantity:**

3

**Hole Type:**

Drilled

**Thready Qty Per Inch (tpi):**

32

**Hole Configuration Style:**

Hexagon corners

**Externally Relieved Body Diameter Quantity:**

1

**Material:**

Steel comp e4340 or steel comp 8740

**Material Specification:**

Mil-s-5000 military specification 1st material response or mil-s-6049 military specification 2nd material response or ams6322 assn standard 2nd material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-s-5000 spec.