## NSN 5305-01-327-5692

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-327-5692 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.425 inches **Fastener Length:** Between 0.848 inches and 0.878 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.449 inches and 0.507 inches **Grip Diameter:** Between 0.2485 inches and 0.2495 inches **Internal Drive Style:** Offset cruciform (torque set) **Thread Diameter:** 0.250 inches **Grip Length:** Between 0.428 inches and 0.448 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 220000 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Material: Nickel alloy 718 **Material Specification:** Ams5662 assn standard single material response **Surface Treatment:** Aluminum **Surface Treatment Specification:** Cagec 73197 spec. 284 mfr ref single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure:** 

**Demilitarization:** No

## NSN 5305-01-327-5692

Close Tolerance Screw - Page 2 of 2



Fiig:

A003b0