NSN 5305-01-327-5693

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-327-5693 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.469 inches **Fastener Length:** Between 1.397 inches and 1.417 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.577 inches and 0.635 inches **Grip Diameter:** Between 0.3110 inches and 0.3120 inches **Internal Drive Style:** Offset cruciform (torque set) **Thread Diameter:** 0.312 inches **Grip Length:** Between 0.923 inches and 0.953 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 16000 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Surface Finish: 32.0 microinches threads Material: Titanium alloy uns r56400 **Material Specification:** Ams4928 assn standard single material response or ams4967 assn standard single material response **Surface Treatment:** Aluminum **Surface Treatment Specification:** Nas4006 assn standard single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a

Unit Of Measure:

NSN 5305-01-327-5693

Close Tolerance Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0