NSN 5305-01-327-9044

Panel Screw Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-327-9044

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.189 inches and 0.199 inches

Fastener Length:

Between 0.905 inches and 0.935 inches

Head Style:

Flat chamfer

Head Diameter:

Between 0.285 inches and 0.315 inches

Head Height:

Between 0.096 inches and 0.116 inches

Internal Drive Style:

Hexagon

Material Accommodated Thickness:

Between 0.126 inches and 0.187 inches

Thread Diameter:

0.164 inches

Width Across Flats:

Between 0.1250 inches and 0.1270 inches

Thready Qty Per Inch (tpi):

32

Material:

Steel comp 304 stand-off

Material Specification:

Qq-s-763 cond a federal specification single material response stand-off or mil-s-23195 military specification single material response

stand-off or ams5639 assn standard single material response stand-off

Surface Treatment:

Passivate stand-off

Surface Treatment Specification:

Qq-p-35 ty1, ty2, ty3, ty4 federal specification single treatment response stand-off

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0

NSN 5305-01-327-9044

Panel Screw Assembly - Page 2 of 2

Mil-std (military Standard):

Mil-s-23195 spec.

