## NSN 5305-01-327-9044



Panel Screw Assembly - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-01-327-9044 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.189 inches and 0.199 inches **Fastener Length:** Between 0.905 inches and 0.935 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.285 inches and 0.315 inches **Head Height:** Between 0.096 inches and 0.116 inches **Internal Drive Style:** Hexagon **Material Accommodated Thickness:** Between 0.126 inches and 0.187 inches **Thread Diameter:** 0.164 inches Width Across Flats: Between 0.1250 inches and 0.1270 inches Thready Qty Per Inch (tpi): 32 Material: Steel comp 304 stand-off **Material Specification:** Qq-s-763 cond a federal specification single material response stand-off or mil-s-23195 military specification single material response stand-off or ams5639 assn standard single material response stand-off **Surface Treatment:** Passivate stand-off **Surface Treatment Specification:** Qq-p-35 ty1, ty2, ty3, ty4 federal specification single treatment response stand-off **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:** 

**Demilitarization:** No

Fiig:

A003b0

## NSN 5305-01-327-9044

Panel Screw Assembly - Page 2 of 2



Mil-std (military Standard):

Mil-s-23195 spec.