## NSN 5305-01-327-9690

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-327-9690

Thread Class:
3a Thread Directions
Thread Direction:
Right-hand Thread Longth
Thread Length:
0.425 inches
Fastener Length:  Between 1,222 inches and 1,252 inches
Head Style:
Flat countersunk
Head Diameter:
Between 0.449 inches and 0.507 inches
Grip Diameter:
Between 0.2485 inches and 0.2495 inches
Internal Drive Style: Offset cruciform (torque set)
Thread Diameter:
0.250 inches
Grip Length:
Between 0.802 inches and 0.822 inches
Thready Qty Per Inch (tpi):
28
Min. Tensile Strength (psi):
160000 pounds per square inch
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Surface Finish:
32.0 microinches threads
Material:
Titanium alloy uns r56400
Material Specification:
Ams4928 assn standard single material response or ams4967 assn standard single material response
Surface Treatment:
Aluminum
Surface Treatment Specification:
Nas4006 assn standard single treatment response
Thread Series Designator:
Unif
Shelf Life:
N/a
Unit Of Measure:

--

## NSN 5305-01-327-9690

Close Tolerance Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0