## NSN 5305-01-328-1684

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-328-1684

Thread Class:
2a
Thread Direction:
Right-hand
Thread Length:
Between 0.125 inches and 0.187 inches
Fastener Length:
Between 0.375 inches and 0.440 inches
Head Style:
Flat chamfer
Head Diameter:
Between 0.218 inches and 0.281 inches
Head Height:
Between 0.093 inches and 0.156 inches
Shoulder Diameter:
0.123 inches first shoulder and 0.124 inches first shoulder
Shoulder Length:
0.250 inches first shoulder and 0.253 inches first shoulder
Internal Drive Style:
Hexagon
Thread Diameter:
0.112 inches
Width Across Flats:
0.078 inches
Thready Qty Per Inch (tpi):
40
Hardness Rating:
32.0 rockwell c and 43.0 rockwell c
Shoulder Shape:
Round first shoulder
Material:
Steel comp xm-7 or steel comp 303
Material Specification:
Astm a493 assn standard 1st material response or astm a582 assn standard 2nd material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:
Unc
Shelf Life:
N/a

## NSN 5305-01-328-1684

Shoulder Screw - Page 2 of 2



		• •			
ш	ın	10	<i>(</i> )+	Measure:	

--

Demilitarization:

No

Fiig:

A003b0