Close Tolerance Screw - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5305-01-328-3797

| Thread Class:  |
|--|
| 3a   |
| Thread Direction:  |
| Right-hand   |
| Thread Length:   |
| 0.425 inches   |
| Fastener Length:   |
| Between 0.785 inches and 0.815 inches  |
| Head Style:  |
| Flat countersunk   |
| Head Diameter:   |
| Between 0.449 inches and 0.507 inches  |
| Grip Diameter:   |
| Between 0.2490 inches and 0.2495 inches  |
| Internal Drive Style:  |
| Offset cruciform (torque set)  |
| Thread Diameter:   |
| 0.250 inches   |
| Grip Length:   |
| Between 0.365 inches and 0.385 inches  |
| Thready Qty Per Inch (tpi):  |
| 28   |
| Min. Tensile Strength (psi):   |
| 160000 pounds per square inch  |
| Countersink Angle:   |
| Between 99.0 degrees and 101.0 degrees   |
| Surface Finish:  |
| 32.0 microinches   |
| Material:  |
| Titanium alloy uns r56400  |
| Material Specification:  |
| Ams4928 assn standard single material response or ams4967 assn standard single material response |
| Thread Series Designator:  |
| Unjf   |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
| <br>Demilitarization:  |
| No   |
| Fiig:  |
| A003b0   |
|  |