## NSN 5305-01-328-4668

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-328-4668

| Thread Class:  |
|--|
| 3a   |
| Thread Direction:  |
| Right-hand   |
| Thread Length:   |
| 1.750 inches   |
| Fastener Length:   |
| Between 1.984 inches and 2.031 inches  |
| Head Style:  |
| Hexagon  |
| Head Height:   |
| Between 0.105 inches and 0.120 inches  |
| Width Between Flats:   |
| Between 0.305 inches and 0.314 inches  |
| Internal Drive Style:  |
| Cross recess type 1  |
| Thread Diameter:   |
| 0.190 inches   |
| Thready Qty Per Inch (tpi):  |
| 32   |
| Min. Tensile Strength (psi):   |
| 160000 pounds per square inch  |
| Screw Material:  |
| Iron alloy 660   |
| Screw Material Specification:  |
| Ams5731 assn standard single material response or ams5737 assn standard single material response |
| Screw Surface Treatment:   |
| Passivate  |
| Screw Surface Treatment Specification:   |
| Qq-p-35 federal specification single treatment response  |
| Bearing Surface Of Head Surface Finish:  |
| 63.0 microinches   |
| Shank Surface Finish:  |
| 32.0 microinches   |
| Thread Surface Finish:   |
| 32.0 microinches   |
| Thread Series Designator:  |
| Unjf   |
| Specification Data:  |
| 80205-nas1802 professional/industrial association standard                                       |
| Shelf Life:  |

N/a

## NSN 5305-01-328-4668

Machine Screw - Page 2 of 2



|  | Of |  |  |  |
|--|----|--|--|--|

--

Demilitarization:

No

Fiig:

A500d0