NSN 5305-01-328-6073

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-328-6073 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.1563 inches and 0.2187 inches **Fastener Length:** Between 0.4693 inches and 0.5347 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.2813 inches and 0.3432 inches **Head Height:** Between 0.1250 inches and 0.1874 inches **Shoulder Diameter:** 0.186 inches first shoulder and 0.187 inches first shoulder **Shoulder Length:** 0.313 inches first shoulder and 0.316 inches first shoulder **Internal Drive Style:** Slot **Thread Diameter:** 0.164 inches Thready Qty Per Inch (tpi): 32 Hardness Rating: 32.0 rockwell c and 43.0 rockwell c **Shoulder Shape:** Round first shoulder Material: Steel comp 303 **Material Specification:** Astm a582 cond. A assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 ty1 federal specification single treatment response **Thread Series Designator:** Unc Shelf Life:

--

N/a

Unit Of Measure:

NSN 5305-01-328-6073

Shoulder Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0