## NSN 5305-01-328-9223

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-328-9223 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 1.846 inches **Fastener Length:** 2.000 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.791 inches and 0.875 inches **Spline Minor Diameter:** Between 0.316 inches and 0.319 inches **Spline Major Diameter:** Between 0.377 inches and 0.380 inches **Spline Width:** Between 0.089 inches and 0.092 inches **Internal Drive Style:** Six spline **Thread Diameter:** 0.500 inches Thready Qty Per Inch (tpi): 13 Min. Tensile Strength (psi): 80000 pounds per square inch Minimum Yield Strength: 40000 pounds per square inch **Countersink Angle:** Between 80.0 degrees and 84.0 degrees Material: Nickel alloy k-500 **Material Specification:** Qq-n-281 cl a federal specification single material response **Thread Series Designator:** Unc **Specification Or Standard:** V type Shelf Life:

N/a

**Unit Of Measure:** 

## NSN 5305-01-328-9223

Socket Head Cap Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0