## NSN 5305-01-329-7806

Machine Screw - Page 1 of 2

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5305-01-329-7806

Thread Class: 3a Thread Direction: Right-hand Thread Length: 0.718 inches Fastener Length: Between 0.734 inches and 0.781 inches Head Style: Hexagon Head Height: Between 0.105 inches and 0.120 inches
Thread Direction:Right-handThread Length:0.718 inchesFastener Length:Between 0.734 inches and 0.781 inchesHead Style:HexagonHexagon
Right-handThread Length:0.718 inchesFastener Length:Between 0.734 inches and 0.781 inchesHead Style:HexagonHexagonHead Height:
Thread Length: 0.718 inches Fastener Length: Between 0.734 inches and 0.781 inches Head Style: Hexagon Head Height:
0.718 inches Fastener Length: Between 0.734 inches and 0.781 inches Head Style: Hexagon Head Height:
Fastener Length:         Between 0.734 inches and 0.781 inches         Head Style:         Hexagon         Head Height:
Between 0.734 inches and 0.781 inches Head Style: Hexagon Head Height:
Head Style: Hexagon Head Height:
Hexagon Head Height:
Head Height:
-
Between 0.105 inches and 0.120 inches
Welle Definition Flates
Width Between Flats:
Between 0.305 inches and 0.314 inches
Internal Drive Style:
Cross recess type 1
End Application:
Fmf; dtf; fnf.
Thread Diameter:
0.190 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
160000 pounds per square inch
Screw Material:
Titanium alloy uns r56400
Screw Material Specification:
Ams 4928 assn standard single material response or ams 4967 assn standard single material response
Bearing Surface Of Head Surface Finish:
63.0 microinches
Shank Surface Finish:
32.0 microinches
Thread Surface Finish:
32.0 microinches
Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

## NSN 5305-01-329-7806

Machine Screw - Page 2 of 2

Fiig: A500d0

