NSN 5305-01-329-9742

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-329-9742

| ····· -········· |
|--|
| Thread Class: |
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 0.403 inches |
| Fastener Length: |
| Between 1.013 inches and 1.043 inches |
| Head Style: |
| Flat countersunk |
| Head Diameter: |
| Between 0.5026 inches and 0.5111 inches |
| Grip Diameter: |
| Between 0.2485 inches and 0.2495 inches |
| Internal Drive Style: |
| Offset cruciform (torque set) |
| Thread Diameter: |
| 0.250 inches |
| Grip Length: |
| Between 0.615 inches and 0.635 inches |
| Thready Qty Per Inch (tpi): |
| 28 |
| Countersink Angle: |
| Between 129.0 degrees and 131.0 degrees |
| Surface Finish: |
| 32.0 microinches threads |
| Material: |
| Titanium alloy uns r56400 |
| Material Specification: |
| Ams 4928 assn standard single material response or ams 4967 assn standard single material response |
| Surface Treatment: |
| Aluminum |
| Surface Treatment Specification: |
| Nas 4006 assn standard single treatment response |
| Thread Series Designator: |
| Unjf |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |

NSN 5305-01-329-9742

Close Tolerance Screw - Page 2 of 2

Fiig: A003b0

