NSN 5305-01-329-9962

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-329-9962 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.564 inches and 0.626 inches **Fastener Length:** Between 0.719 inches and 0.750 inches **Head Style:** Oval countersunk **Head Diameter:** Between 0.333 inches and 0.385 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 62000 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Screw Material:** Aluminum alloy 2024 **Screw Material Specification:** Qq-a-225/6 federal specification single material response **Head Surface Treatment:** Paint **Screw Surface Treatment:** Anodize **Head Surface Treatment Specification:** 595 no.23531 federal standard single treatment response **Screw Surface Treatment Specification:** Mil-a-8625 type 1 cl 1 military specification single treatment response **Special Features:** Painted area beige **Thread Series Designator:** Unf Shelf Life:

N/a

Unit Of Measure:

NSN 5305-01-329-9962

Machine Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A500d0

Mil-std (military Standard):

Mil-a-8625 spec.