## NSN 5305-01-329-9963

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-329-9963

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.689 inches and 0.751 inches
Fastener Length:
Between 0.844 inches and 0.875 inches
Head Style:
Oval countersunk
Head Diameter:
Between 0.333 inches and 0.385 inches
Internal Drive Style:
Cross recess type 1
Thread Diameter:
0.190 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
62000 pounds per square inch
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Screw Material:
Aluminum alloy 2024
Screw Material Specification:
Qq-a-225/6 federal specification single material response
Head Surface Treatment:
Paint
Screw Surface Treatment:
Anodize
Head Surface Treatment Specification:
595 no.23531 federal standard single treatment response
Screw Surface Treatment Specification:
Mil-a-8625 type 1 cl 1 military specification single treatment response
Special Features:
Painted area beige
Thread Series Designator:
Unf
Shelf Life:
N/a
Unit Of Measure:

--

## NSN 5305-01-329-9963

Machine Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A500d0

Mil-std (military Standard):

Mil-a-8625 spec.