NSN 5305-01-330-0429

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-330-0429 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.350 inches **Fastener Length:** 0.500 inches **Head Style:** Flat chamfer **Head Diameter:** 0.380 inches **Head Height:** 0.500 inches **Shank Unthreaded Hole Diameter:** 0.120 inches first hole First Diameter From Head: 0.170 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.150 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.250 inches Width Across Flats: Between 0.188 inches and 0.190 inches Thready Qty Per Inch (tpi): Distance From Head Largest Bearing Surface To Shank Hole Center: 0.340 inches first hole **Externally Relieved Body Diameter Quantity:** Material: Nickel alloy k-500 **Material Specification:** Qq-n-286 cl a federal specification single material response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:**

--

NSN 5305-01-330-0429

Externally Relieved Body Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0