NSN 5305-01-330-2313

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-330-2313

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.688 inches and 0.750 inches
Fastener Length:
Between 0.720 inches and 0.750 inches
Head Style:
Flat chamfer
Head Diameter:
Between 0.218 inches and 0.226 inches
Head Height:
Between 0.134 inches and 0.138 inches
Locking Feature:
Strip threads
Internal Drive Style:
Hexagon
Thread Diameter:
0.138 inches
Width Across Flats:
Between 0.1094 inches and 0.1111 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
160000 pounds per square inch
Hardness Rating:
33.0 rockwell c fastener and 42.0 rockwell c fastener
Minimum Yield Strength:
120000 pounds per square inch
Material:
Plastic polyamide locking feature
Material Specification:
Ams5731 assn standard single material response fastener or ams5737 assn standard single material response fastener
Surface Treatment:
Passivate fastener
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response fastener
Thread Series Designator:
Unrc
Specification Data:

80205-nas1352 professional/industrial association standard

NSN 5305-01-330-2313

Socket Head Cap Screw - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J	116		_	.II C.	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0