

View Online at <https://aerobasegroup.com/nsn/5305-01-330-2314>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.688 inches and 0.750 inches

Fastener Length:

Between 0.970 inches and 1.000 inches

Head Style:

Flat chamfer

Head Diameter:

Between 0.176 inches and 0.181 inches

Head Height:

Between 0.108 inches and 0.112 inches

Locking Feature:

Strip threads

Internal Drive Style:

Hexagon

Thread Diameter:

0.138 inches

Width Across Flats:

Between 0.1094 inches and 0.1111 inches

Thread Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

160000 pounds per square inch

Hardness Rating:

33.0 rockwell c fastener and 42.0 rockwell c fastener

Minimum Yield Strength:

120000 pounds per square inch

Material:

Plastic polyamide locking feature

Material Specification:

Ams 5731 assn standard single material response fastener or ams 5737 assn standard single material response fastener

Surface Treatment:

Passivate fastener

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response fastener

Thread Series Designator:

Unrc

Specification Data:

80205-nas1352 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0