NSN 5305-01-330-3164

Thread Class:

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-330-3164

| 3a |
|---|
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 1.712 inches |
| Fastener Length: |
| 1.750 inches |
| Head Style: |
| Flat chamfer |
| Head Diameter: |
| Between 0.735 inches and 0.750 inches |
| Head Height: |
| Between 0.492 inches and 0.500 inches |
| Hole Diameter: |
| 0.120 inches |
| Locking Feature: |
| Pellet threads or strip threads or patch threads |
| Internal Drive Style: |
| Hexagon |
| Thread Diameter: |
| 0.500 inches |
| Width Across Flats: |
| 0.375 inches |
| Hole Quantity: |
| 6 |
| Hole Type: |
| Drilled |
| Thready Qty Per Inch (tpi): |
| 13 |
| Min. Tensile Strength (psi): |
| 180000 pounds per square inch |
| Hardness Rating: |
| 39.0 rockwell c fastener and 45.0 rockwell c fastener |
| Hole Configuration Style: |
| Round internal hexagon |
| Material: |
| Steel fastener |
| Material Specification: |
| Astm a574 assn standard single material response fastener |

Surface Treatment:

Aluminum fastener or chromate zinc fastener

NSN 5305-01-330-3164

Socket Head Cap Screw - Page 2 of 2



Surface Treatment Specification:

Mil-c-83488 type 2 cl 3 military specification 1st treatment response fastener or mil-c-87115 cl 3 military specification 2nd treatment response fastener

| eries D | esignato | r: |
|---------|----------|-----------------|
| | eries D | eries Designato |

Unrc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-83488 spec.