NSN 5305-01-330-7074

Fiig: A003b0

Externally Relieved Body Screw - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5305-01-330-7074 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.365 inches and 0.385 inches **Fastener Length:** Between 1.110 inches and 1.140 inches **Head Style:** Knurled no. 1 **Head Diameter:** Between 0.735 inches and 0.765 inches **Head Height:** Between 0.240 inches and 0.260 inches **First Diameter From Head:** Between 0.182 inches and 0.192 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.500 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 Material: Copper alloy 274 or copper alloy 353 or copper alloy 360 or copper alloy 377 or copper alloy 462 or copper alloy 464 or copper alloy 482 or copper alloy 485 **Surface Treatment:** Nickel **Surface Treatment Specification:** Qq-n-290 federal specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure: Demilitarization:** No