Externally Relieved Body Screw - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5305-01-330-7074

Thread Class:	
2a	
Thread Direction:	
Right-hand	
Thread Length:	
Between 0.365 inches and	0.385 inches
Fastener Length:	
Between 1.110 inches and	1.140 inches
Head Style:	
Knurled no. 1	
lead Diameter:	
Between 0.735 inches and	0.765 inches
lead Height:	
Between 0.240 inches and	0.260 inches
First Diameter From Hea	1:
Between 0.182 inches and	0.192 inches
Distance From Largest B	earing Surface Of Head To End Of First Diameter:
0.500 inches	
nternal Drive Style:	
Slot	
Thread Diameter:	
).250 inches	
Thready Qty Per Inch (tp):
0	
Externally Relieved Body	Diameter Quantity:
I	
Material:	
Copper alloy 274 or coppe	r alloy 353 or copper alloy 360 or copper alloy 377 or copper alloy 462 or copper alloy 464 or copper alloy 482
or copper alloy 485	
Surface Treatment:	
Nickel	
Surface Treatment Speci	ication:
Qq-n-290 federal specifica	ion single treatment response
Thread Series Designato	·
Unc	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A003b0	