NSN 5305-01-331-0032

Machine Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-01-331-0032



Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.100 inches and 0.193 inches

Fastener Length:

Between 0.219 inches and 0.250 inches

Head Style:

Flat countersunk

Head Diameter:

0.057 inches

Locking Feature:

Patch

Internal Drive Style:

Cross recess type 1

Thread Diameter:

0.138 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

160000 pounds per square inch

Hardness Rating:

Between 36.0 rockwell c and 40.0 rockwell c

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Screw Material:

Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150

Locking Feature Material:

Plastic polyamide

Screw Surface Treatment:

Cadmium and chromate

Screw Surface Treatment Specification:

Qq-p-416, ty2 cl2 federal specification single treatment response

Thread Series Designator:

Unjc

Specification Data:

80205-nas1189 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

NSN 5305-01-331-0032

Machine Screw - Page 2 of 2

Demilitarization:

No

Fiig:

A500d0

