## NSN 5305-01-331-1249

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-331-1249 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.290 inches and 0.330 inches **Fastener Length:** Between 0.900 inches and 1.000 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.176 inches and 0.183 inches **Head Height:** Between 0.108 inches and 0.112 inches **First Diameter From Head:** Between 0.075 inches and 0.085 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.660 inches and 0.710 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.112 inches Width Across Flats: Between 0.094 inches and 0.095 inches Thready Qty Per Inch (tpi): 40 **Externally Relieved Body Diameter Quantity:** Material: Steel comp 302 or steel comp 304 or steel comp 305 or steel comp 316 or steel comp 384 or steel comp xm-7 **Material Specification:** Astm a493 assn standard all material responses **Surface Treatment:** Oxide **Surface Treatment Specification:** Mil-c-13924 cl4 military specification single treatment response **Thread Series Designator:** Unrc Shelf Life: N/a

-

**Unit Of Measure:** 

## NSN 5305-01-331-1249

Externally Relieved Body Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-13924 spec.