NSN 5305-01-331-1250

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-331-1250 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.150 inches and 0.155 inches **Fastener Length:** Between 0.470 inches and 0.500 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.218 inches and 0.226 inches **Head Height:** Between 0.134 inches and 0.138 inches **First Diameter From Head:** Between 0.100 inches and 0.105 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.315 inches and 0.350 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.138 inches Width Across Flats: Between 0.188 inches and 0.190 inches Thready Qty Per Inch (tpi): 32 **Externally Relieved Body Diameter Quantity:** Color: Black Material: Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316 **Material Specification:** 66 federal standard all material responses **Surface Treatment:** Oxide **Surface Treatment Specification:** Mil-c-13924 cl 4 military specification single treatment response **Thread Series Designator:** Unc

N/a

Shelf Life:

NSN 5305-01-331-1250

Externally Relieved Body Screw - Page 2 of 2



Unit Of Measure	:
-----------------	---

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-13924 spec.