## NSN 5305-01-331-3228

Machine Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-01-331-3228



**Thread Class:** 3a **Thread Direction: Right-hand Thread Length:** 0.438 inches **Fastener Length:** Between 0.469 inches and 0.500 inches **Head Style:** Pan **Head Diameter:** Between 0.306 inches and 0.322 inches **Head Height:** Between 0.105 inches and 0.115 inches Locking Feature: Strip **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.164 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch **Product Name:** Navy special project **Screw Material:** Iron alloy 660 Locking Feature Material: Plastic polychlorotrifluoroethylene **Screw Material Specification:** Ams 5737 assn standard single material response Locking Feature Material Specification: Ams 3650 assn standard single material response **Screw Surface Treatment:** Cadmium and chromate **Screw Surface Treatment Specification:** Qq-p-416, type 2 cl 2 federal specification single treatment response **Thread Series Designator:** Unjc **Specification Data:** 

80205-nas1190 professional/industrial association standard

## NSN 5305-01-331-3228

Machine Screw - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A500d0

