

View Online at <https://aerobasegroup.com/nsn/5305-01-331-5796>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.845 inches and 1.000 inches

Fastener Length:

Between 0.970 inches and 1.000 inches

Head Style:

Flat chamfer

Head Diameter:

Between 0.550 inches and 0.563 inches

Head Height:

Between 0.360 inches and 0.375 inches

Internal Drive Style:

Hexagon

Thread Diameter:

0.375 inches

Width Across Flats:

Between 0.3125 inches and 0.3160 inches

Thready Qty Per Inch (tpi):

16

Criticality Code Justification:

Zzzy

Special Features:

Item must comply with requirements of defense supply center philadelphia production standard no. Po0094nrp

Material:

Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316

Material Specification:

66 federal standard all material responses

Surface Treatment:

Passivate

Special Test Features:

Special quality control testing

Surface Treatment Specification:

Qq-p-35 ty2 federal specification single treatment response

Test Data Document:

81349-mil-p-23199 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unc

Reference Number Differentiating Characteristics:

Areference number differentiating material will be in accordance with naval inventory control point activity hx quality control. Manufacturing and testing specifications available at the dla icp

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0