NSN 5305-01-331-7188

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-331-7188 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.160 inches **Fastener Length:** Between 0.469 inches and 0.500 inches **Head Style:** Pan no. 2 **Head Diameter:** Between 0.256 inches and 0.270 inches **Head Height:** 0.077 inches **First Diameter From Head:** 0.106 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.340 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 70000 pounds per square inch **Externally Relieved Body Diameter Quantity:** Material: Steel comp 304 or steel comp 305 or steel comp 310 or steel comp 316 or steel comp 316l or steel comp 322 or steel comp 324 or steel comp 303 or steel comp 403 or steel comp 416 or steel comp 430 **Material Specification:** Qq-a-763 federal specification all material responses **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unc

--

N/a

Shelf Life:

Unit Of Measure:

NSN 5305-01-331-7188

Externally Relieved Body Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0