## NSN 5305-01-331-7552

Externally Relieved Body Screw - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5305-01-331-7552 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.312 inches and 0.333 inches **Fastener Length:** Between 0.719 inches and 0.750 inches **Head Style:** Pan **Head Diameter:** Between 0.357 inches and 0.373 inches **Head Height:** Between 0.122 inches and 0.133 inches First Diameter From Head: Between 0.133 inches and 0.143 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.407 inches and 0.417 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 Material: Steel comp 301 or steel comp 302 or steel comp 302b or steel comp 303 or steel comp 303se or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 308 or steel comp 309 or steel comp 309s or steel comp 310 or steel comp 310s or steel comp 314 or steel comp 316 or steel comp 316l or steel comp 317 or steel comp 321 or steel comp 348 or steel comp 384 or steel comp comp 385 **Surface Treatment: Passivate Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:** 

No Fiig:

•

**Demilitarization:** 

A003b0