

View Online at <https://aerobasegroup.com/nsn/5305-01-331-8590>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 0.302 inches and 0.322 inches

Fastener Length:

Between 0.885 inches and 0.925 inches

Head Style:

Flat chamfer

Head Diameter:

Between 0.359 inches and 0.391 inches

Head Height:

Between 0.172 inches and 0.204 inches

First Diameter From Head:

Between 0.131 inches and 0.136 inches

Distance From Largest Bearing Surface Of Head To End Of First Diameter:

Between 0.583 inches and 0.603 inches

Internal Drive Style:

Slot

Thread Diameter:

0.190 inches

Thready Qty Per Inch (tpi):

32

Externally Relieved Body Diameter Quantity:

1

Material:

Steel comp 301 or steel comp 302 or steel comp 302b or steel comp 303 or steel comp 303se or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 308 or steel comp 309 or steel comp 309s or steel comp 310 or steel comp 310s or steel comp 314 or steel comp 316 or steel comp 316l or steel comp 317 or steel comp 321 or steel comp 347 or steel comp 348 or steel comp 384 or steel comp 385

Surface Treatment:

Passivate

Surface Treatment Specification:

Astm a380 assn standard single treatment response

Thread Series Designator:

Unf

Specification Or Standard:

1 type and 4s style

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0