NIo

Externally Relieved Body Screw - Page 1 of 2

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5305-01-331-8590

Thread Class:	
2a	
Thread Direction:	
Right-hand	
Thread Length:	
Between 0.302 inche	s and 0.322 inches
Fastener Length:	
Between 0.885 inche	s and 0.925 inches
Head Style:	
Flat chamfer	
Head Diameter:	
Between 0.359 inche	s and 0.391 inches
Head Height:	
Between 0.172 inche	s and 0.204 inches
First Diameter From) Head:
Between 0.131 inche	s and 0.136 inches
Distance From Larg	est Bearing Surface Of Head To End Of First Diameter:
Between 0.583 inche	s and 0.603 inches
Internal Drive Style:	
Slot	
Thread Diameter:	
0.190 inches	
Thready Qty Per Inc	sh (tpi):
32	
Externally Relieved	Body Diameter Quantity:
1	
Material:	
Steel comp 301 or st	teel comp 302 or steel comp 302b or steel comp 303 or steel comp 303se or steel comp 304 or steel comp 304l or
steel comp 305 or st	eel comp 308 or steel comp 309 or steel comp 309s or steel comp 310 or steel comp 310s or steel comp 314 or
steel comp 316 or st	eel comp 316l or steel comp 317 or steel comp 321 or steel comp 347 or steel comp 348 or steel comp 384 or stee
comp 385	
Surface Treatment:	
Passivate	
Surface Treatment S	
	dard single treatment response
Thread Series Desig	gnator:
Unf	
Specification Or Sta	indard:
1 type and 4s style	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	

NSN 5305-01-331-8590

Externally Relieved Body Screw - Page 2 of 2

Fiig: A003b0

