NSN 5305-01-331-8590

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-331-8590 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.302 inches and 0.322 inches **Fastener Length:** Between 0.885 inches and 0.925 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.359 inches and 0.391 inches **Head Height:** Between 0.172 inches and 0.204 inches **First Diameter From Head:** Between 0.131 inches and 0.136 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.583 inches and 0.603 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 Material: Steel comp 301 or steel comp 302 or steel comp 302b or steel comp 303 or steel comp 303se or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 308 or steel comp 309 or steel comp 309s or steel comp 310 or steel comp 310s or steel comp 314 or steel comp 316 or steel comp 316l or steel comp 317 or steel comp 321 or steel comp 348 or steel comp 384 or steel comp comp 385 **Surface Treatment: Passivate Surface Treatment Specification:** Astm a380 assn standard single treatment response **Thread Series Designator:** Unf **Specification Or Standard:** 1 type and 4s style Shelf Life:

NIa

N/a

Unit Of Measure:

Demilitarization:

NSN 5305-01-331-8590

Externally Relieved Body Screw - Page 2 of 2



Fiig:

A003b0