NSN 5305-01-332-0886

Close Tolerance Screw - Page 1 of 2



view Online at https://aerobasegroup.com/nsn/5305-01-332-0666
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.323 inches
Fastener Length:
Between 0.808 inches and 0.838 inches
Head Style:
Pan
Head Diameter:
Between 0.357 inches and 0.373 inches
Head Height:
Between 0.122 inches and 0.133 inches
Grip Diameter:
Between 0.1885 inches and 0.1895 inches
Internal Drive Style:
Cross recess type 1
Thread Diameter:
0.190 inches
Grip Length:
Between 0.490 inches and 0.510 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
160000 pounds per square inch
Material:
Steel comp e4340 or steel comp 8740
Material Specification:
Mil-s-5000 military specification 1st material response or mil-s-6049 military specification 2nd material response or ams6322 assn standard
2nd material response
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416 ty2 cl2 federal specification single treatment response
Thread Series Designator:
Unjf
Specification Data:
80205-nas7703 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:

NSN 5305-01-332-0886

Close Tolerance Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5000 spec.