NSN 5305-01-332-2155

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-332-2155 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.100 inches **Fastener Length:** 0.250 inches **Head Style:** Fillister **Head Diameter:** Between 0.134 inches and 0.140 inches **Head Height:** 0.086 inches **First Diameter From Head:** 0.086 inches **Second Diameter From Head:** Between 0.057 inches and 0.062 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.020 inches and 0.030 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.380 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.086 inches Width Across Flats: 0.0781 inches Thready Qty Per Inch (tpi): 56 Minimum Yield Strength: 80000 pounds per square inch **Externally Relieved Body Diameter Quantity:** 1 Material: Steel comp 303 **Material Specification:** Astm a582 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

NSN 5305-01-332-2155

Externally Relieved Body Screw - Page 2 of 2



Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A003b0