## NSN 5305-01-332-3167

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-332-3167

| g  |
|--|
| Thread Class:  |
| 3a   |
| Thread Direction:  |
| Right-hand   |
| Thread Length:   |
| Between 0.360 inches and 0.414 inches  |
| Fastener Length:   |
| Between 0.422 inches and 0.454 inches  |
| Head Style:  |
| Flat chamfer   |
| Head Diameter:   |
| Between 0.303 inches and 0.312 inches  |
| Head Height:   |
| Between 0.185 inches and 0.190 inches  |
| Internal Drive Style:  |
| Hexagon  |
| Thread Diameter:   |
| 0.190 inches   |
| Width Across Flats:  |
| Between 0.375 inches and 0.390 inches  |
| Thready Qty Per Inch (tpi):  |
| 32   |
| Min. Tensile Strength (psi):   |
| 160000 pounds per square inch  |
| Hardness Rating:   |
| 33.0 rockwell c and 42.0 rockwell c  |
| Minimum Yield Strength:  |
| 120000 pounds per square inch  |
| Material:  |
| Iron alloy 660   |
| Material Specification:  |
| Ams5731 assn standard single material response or ams5737 assn standard single material response |
| Surface Treatment:   |
| Passivate  |
| Surface Treatment Specification:   |
| Qq-p-35 federal specification single treatment response  |
| Thread Series Designator:  |
| Unjf   |
| Specification Data:  |
| 80205-nas1351 professional/industrial association standard                                       |
| Shelf Life:  |
|  |

N/a

## NSN 5305-01-332-3167

Socket Head Cap Screw - Page 2 of 2



|  |  | eas |  |
|--|--|-----|--|

--

Demilitarization:

No

Fiig:

A003b0