# NSN 5305-01-332-6672

Machine Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-01-332-6672



# Thread Class:

3a

**Thread Direction:** 

Right-hand

## Thread Length:

Between 1.750 inches and 2.093 inches

# Fastener Length:

Between 2.046 inches and 2.093 inches

## Head Style:

Hexagon

Head Height:

Between 0.105 inches and 0.120 inches

## Width Between Flats:

Between 0.305 inches and 0.314 inches

# Internal Drive Style:

Cross recess type 1

## Thread Diameter:

0.190 inches

#### Thready Qty Per Inch (tpi):

32

#### Min. Tensile Strength (psi):

160000 pounds per square inch

## Screw Material:

Iron alloy 660

## Screw Material Specification:

Ams5731 assn standard single material response or ams5732 assn standard single material response

#### **Screw Surface Treatment:**

Passivate

## Screw Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

## Bearing Surface Of Head Surface Finish:

63.0 microinches

#### Shank Surface Finish:

32.0 microinches

#### **Thread Surface Finish:**

32.0 microinches

#### **Thread Series Designator:**

Unjf

# Specification Data:

80205-nas1802 professional/industrial association standard

# Shelf Life:

N/a

# NSN 5305-01-332-6672

Machine Screw - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A500d0

