

View Online at <https://aerobasegroup.com/nsn/5305-01-332-7187>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.145 inches and 0.195 inches

**Fastener Length:**

Between 0.280 inches and 0.310 inches

**Head Style:**

Pan

**Head Diameter:**

Between 0.205 inches and 0.219 inches

**Head Height:**

Between 0.070 inches and 0.090 inches

**First Diameter From Head:**

Between 0.078 inches and 0.082 inches

**Distance From Largest Bearing Surface Of Head To End Of First Diameter:**

Between 0.115 inches and 0.135 inches

**Internal Drive Style:**

Cross recess type 1

**Thread Diameter:**

0.112 inches

**Thready Qty Per Inch (tpi):**

40

**Hardness Rating:**

36.0 rockwell c and 40.0 rockwell c

**Externally Relieved Body Diameter Quantity:**

1

**Material:**

Steel comp 4140 or steel comp e4340 or steel comp 8740

**Material Specification:**

Mil-s-5626 military specification 1st material response or mil-s-5000 military specification 2nd material response or mil-s-6049 military specification 3rd material response

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Qq-p-416 type 2, cl 3 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0

**Mil-std (military Standard):**

Mil-s-5626 spec.