NSN 5305-01-332-7187

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-332-7187 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.145 inches and 0.195 inches **Fastener Length:** Between 0.280 inches and 0.310 inches **Head Style:** Pan **Head Diameter:** Between 0.205 inches and 0.219 inches **Head Height:** Between 0.070 inches and 0.090 inches **First Diameter From Head:** Between 0.078 inches and 0.082 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.115 inches and 0.135 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.112 inches Thready Qty Per Inch (tpi): 40 Hardness Rating: 36.0 rockwell c and 40.0 rockwell c **Externally Relieved Body Diameter Quantity:** Material: Steel comp 4140 or steel comp e4340 or steel comp 8740 **Material Specification:** Mil-s-5626 military specification 1st material response or mil-s-5000 military specification 2nd material response or mil-s-6049 military specification 3rd material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416 type 2, cl 3 federal specification single treatment response **Thread Series Designator:** Unjf

--

N/a

Shelf Life:

Unit Of Measure:

NSN 5305-01-332-7187

Externally Relieved Body Screw - Page 2 of 2



_		 • •				
n	em	it o	riz	2 †1	n	٠.

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5626 spec.